**Note:** This report is issued subject to the Testing and Certification Regulations of the TÜV SÜD Group and the General Terms and Conditions of Business of TÜV SÜD PSB Pte Ltd. In addition, this report is governed by the terms set out within this report.

#### Subject:

Testing of Office Chair submitted by Merryfair Chair System Sdn Bhd on 26 Apr 2012.

#### Tested For:

Merryfair Chair System Sdn Bhd No 2, Jalan Koporat 1/KU9, Taman Perindustrian Meru, 42200 Klang, Selangor D.E. Malaysia

#### Date of Test:

30 Apr 2012 to 09 Jul 2012

#### **Description of Sample:**

Two complete sets of Chair as shown in the photograph 1 were received. The following descriptions were given by the client:

Model	1	Robin
Product Type	:	Office Chair
Country of Origin	:	Malaysia

#### Method of Test:

As requested by the client, the tests were conducted in accordance with the following standard:

ANSI/BIFMA X5.1 - 2011 "General-Purpose Office Chairs - Tests"

The tests were conducted at TÜV SÜD PSB furniture test laboratory, a FIRA (UK) Accredited Testing Laboratory, located at No.1 Science Park Drive. Singapore 118221.

I fl



Laboratory: TÜV SÜD PSB Pte. Ltd. No.1 Science Park Drive Singapore 118221 Phone : +65-6885 1333 Fax : +65-6776 8670 E-mail: testing@tuv-sud-psb.sg www.tuv-sud-psb.sg Co. Reg : 199002667R Regional Head Office: TÜV SÜD Asia Pacific Pte. Ltd. 3 Science Park Drive, #04-01/05 The Franklin, Singapore 118223



Choose certainty. Add value.



# Results:

Clause	Test	Parameters	Results	Requirement
5	Back Strength Test – Static – Type I	Functional load = Proof load = Duration =	N/A	Functional load: No loss of serviceability Proof Load:
6	Back Strength Test – Static – Type III	Functional load = 667 N Proof load = 1112 N Duration = 1 min	Passed	No sudden & major change in structural integrity. Loss of serviceability is acceptable
7	Base Test – Static	Loading force = Duration = Cycles =	N/A	No sudden & major change in the structural integrity of the base.
8	Drop Test – Dynamic	Functional load = 102 kg Proof load = 136 kg Drop ht = 152 mm	Passed	Functional load: No loss of serviceability Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable
9	Swivel Test – Cyclic	Seat load = Total cycles = Rate =	N/A	No loss of serviceability
10	Tilt Mechanism Test – Cyclic	Seat load = Cycles = Rate =	N/A	No loss of serviceability to the tilt mechanism
11	Seating Durability test – Cyclic - Impact Test - Front Corner Load-Ease Test – Cyclic – Off Center	Seat load = 57 kg Drop ht = 30 mm Cycles = 100000 Rate = 10 - 30 cycles/min Seat load = 734 N Cycle = 40000 Rate = 10 - 30 cycles/min	Passed	No loss of serviceability

orfe



# Results:

Clause	Test	Parameters	Results	Requirement
12	Stability Tests - a) Rear Stability i) Type III b) Front Stability	Loading = $\underline{60}$ kg Force = $\underline{145}$ N Vertical Load = 600 N	Passed	Chair shall not tip over.
13	Arm Strength Test – Vertical – Static	Horizontal force = 20 N Functional load = 750 N Proof load = 1125 N Duration = 1 min	Passed	Functional load: No loss of serviceability. For a height adjustable arm, it must hold the position within 6mm. Proof Load: No sudden & major change in structural integrity. For a height adjustable arm, it must not has a sudden drop in height of greater than 25mm. Loss of serviceability is acceptable
14	Arm Strength Test – Horizontal – Static	Functional load = 445 N Proof load = 667 N Duration = 1 min	Passed	Functional load: No loss of serviceability. Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable

orfe



# Results:

Clause	Test	Parameters	Results	Requirement	
15	Back Durability Test – Cyclic – Type I	Seat weight = Loading force = Cycles = Rate =	N/A	No loss of serviceability	
16	Back Durability Test – Cyclic – Type III	Seat weight = 102 kg Loading force = 334 N Cycles = 120000 Rate = 10-30 cycles/min	Passed		
17	Caster / Chair Base Durability Test – Cyclic - Pedestal Base Chairs - Chairs with Legs	Seat weight = Cycles: 2000 (Obstacles) 98000 (No obstacles) Rate =	N/A		
	Caster Retention for Each Caster	Applied force =	N/A	No part of castor shall separate from base	
18	Leg Strength Test – Front & Side Application - Front Load Test - Side Load Test	Functional load = Proof load = Duration = Functional load = Proof load = Duration =	N/A	Functional load: No loss of serviceability Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable	
19	Footrest Static Load Test – Vertical	Functional Load, Force, F1 = Footrest adjustment, Force F1 = Force, F2 = Duration = Proof Load, Force = Duration =	N/A	Functional Load: No loss of serviceability or sudden loss of footrest height. Proof Load: No sudden & major change in structural integrity. Loss of serviceability is acceptable	



# Results:

Clause	Test	Parameters	Results	Requirement
20	Footrest Durability Test – Vertical – Cyclic	Loading force = Cycles = Rate =	N/A	No loss of serviceability. Adjustable footrest that move more than 25mm in the first 500 cycles shall be considered to have lost their serviceability.
21	Arm Durability Test – Cyclic	Applied force = 400 N Cycles = 60000 Rate = 10 - 30 cycles/min	Passed	No loss of serviceability.
22	Out Stop Tests for Chairs with Manually Adjustable Seat Depth	Seat weight = Loading weight = Cycles =	N/A	
23	Tablet Arm Static Load Test	Applied load = Duration =	N/A	No sudden and major change in the structural integrity of the chair. After test, tablet arm must allow egress from the unit; other losses of serviceability are acceptable
24	Tablet Arm Load Ease Test – Cyclic	Force = Cycles = Rate =	N/A	No loss of serviceability

### Remarks:

1) N/A: Not applicable due to features not available on chair.

Gavin Ong

Associate Engineer

Chin Fook Onn Product Manager Consumer & Safety Products Mechanical Centre





Photograph 1 : Robin

orfe



Please note that this Report is issued under the following terms :

- 1. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment. Unless otherwise stated in this report, no tests were conducted to determine long term effects of using the specific product/equipment.
- 2. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
- 3. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
- 4. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
- 5. Unless otherwise stated, the tests were carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.



